

View Online at <https://aerobasegroup.com/nsn/4720-00-148-0823>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.880 inches

Flange Thickness:

0.270 inches and 0.280 inches 2nd end

Outside Diameter:

2.030 inches

Minimum Inside Bending Radius:

4.000 inches

Center To Center Distance Between Bolt Holes Along Width:

1.500 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

1.500 inches 2nd end

Bolt Hole Quantity:

4 2nd end

Flange Length:

1.550 inches 2nd end

Flange Width:

1.550 inches 2nd end

Connection Style:

Swivel nut flare 1st end

Bolt Hole Diameter:

0.266 inches and 0.276 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 1st end

Maximum Operating Pressure:

750.0 pounds per square inch

Thread Size:

1.312 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

1250.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

19.000 inches working

Flange Style:

Rectangular (includes square) 2nd end

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0