NSN 4720-00-150-6131

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-150-6131

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.602 inches |
| Tempurature Rating: |
| -67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.884 inches |
| Minimum Inside Bending Radius: |
| 3.880 inches |
| Connection Style: |
| Swivel nut, flareless 2nd end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Burst Test Pressure: |
| 12000.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer braided corrosion resistant steel wire |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch |
| Thread Size: |
| 1.062 inches 2nd end |
| Seat Angle: |
| 12.0 degrees 2nd end |
| Hydrostatic Test Pressure: |
| 6000.0 pounds per square inch |
| Flow Angle: |
| 90.0 degrees 2nd end |
| Outer Covering Environmental Protection: |
| Fuel resistant and oil resistant and solvent resistant and vibration resistant and heat resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 27.000 inches |
| Thread Series Designator: |
| Unit 1st and |

Unjf 1st end

NSN 4720-00-150-6131

Nonmetallic Hose Assembly - Page 2 of 2



| - | | | | | |
|---|----|----|----|---|---|
| • | he | 1+ | 18 | Δ | • |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0