NSN 4720-00-152-1182

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches

Tempurature Rating:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-152-1182

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response	
Outside Diameter:	
0.312 inches	
Minimum Inside Bending Radius:	
2.000 inches	
Exterior Color:	
Natural	
Connection Style:	
Swivel nut flare 2nd end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Reusable end fittings	
Burst Test Pressure:	
12000.0 pounds per square inch	
Layer Composition And Location:	
Outer layer braided corrosion resistant steel wire	
Maximum Operating Pressure:	
1500.0 pounds per square inch	
Thread Size:	
0.438 inches 1st end	
Seat Angle:	
37.0 degrees 2nd end	
Hydrostatic Test Pressure:	
3000.0 pounds per square inch	
Flow Angle:	
45.0 degrees 2nd end	
Outer Covering Environmental Protection:	
Corrosion resistant	
Vacuum In Torr:	
50.8	

NSN 4720-00-152-1182

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:
Smooth
Measuring Method And Length:
7.125 inches working
Thread Series Designator:
Unf 2nd end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0