NSN 4720-00-161-7582

Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-161-7582

Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.688 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response
Outside Diameter:
0.938 inches
Minimum Inside Bending Radius:
4.500 inches
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 2nd end
Burst Test Pressure:
3750.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
1.062 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
2000.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant
Vacuum In Torr:
76.2
Inside Surface Condition:
Smooth
Measuring Method And Length:
17.125 inches working
Media For Which Designed:
Fuel/oil, hydrocarbon single response

NSN 4720-00-161-7582

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Unj 2nd end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Demilitarization:

Mil-std (military Standard):

Mil-h-83796 spec.