

View Online at <https://aerobasegroup.com/nsn/4720-00-161-7615>

Cross Sectional Shape:

Round

Thread Direction:

Left-hand 1st end

Inside Diameter:

0.250 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.690 inches

Minimum Inside Bending Radius:

4.000 inches

Exterior Color:

Black

Connection Style:

Swivel nut, gas 2nd end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting stainless steel all ends

Connection Type:

Threaded internal gas cylinder 2nd end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

20000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

2nd layer braided wire

Maximum Operating Pressure:

5000.0 pounds per square inch

Thread Size:

0.830 inches 2nd end

Seat Angle:

30.0 degrees 1st end

Flow Angle:

90.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

68.000 inches

Second End Swivel Action Capability:

Not included

Seat Radius:

0.156 inches 2nd end

Special Features:

Inner conveying tube material-rubber, synthetic; furnished with special straight gas cylinder fitting with strainer screen on one end, and with special elbow gas cylinder fitting with strainer screen and gage on other end; furnished with special straight

Media For Which Designed:

Gas single response

Thread Series Designator:

Ngo 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0