Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-162-1978

Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.312 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single resp	ponse
Outside Diameter:	
0.609 inches	
Minimum Inside Bending Radius:	
1.250 inches	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 2nd end	
Connection Type:	
Threaded internal tube 1st end	
Thready Qty Per Inch (tpi):	
18 1st end	
Burst Test Pressure:	
4000.0 pounds per square inch	
Layer Composition And Location:	
2nd layer braided steel wire and outer layer rubber impregnated be	raided fabric and 1st layer braided cotton cord
Maximum Operating Pressure:	
1000.0 pounds per square inch	
Thread Size:	
0.625 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressure:	
2000.0 pounds per square inch	
Outer Covering Environmental Protection:	
Oil resistant and ozone resistant	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
44.250 inches	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	

Nonmetallic Hose Assembly - Page 2 of 2



**Thread Series Designator:** 

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0