Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-162-8314

Cross Sectional Shape: Round Thread Direction: Right-hand 1st end Inside Diameter: 0.500 inches Tempurature Rating: -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.750 inches Minimu Inside Bending Radius: 5.000 inches Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Burst Test Pressure: 50.0.0 pounds per square inch Layer Composition And Location: Outo pounds per square inch Hared Size: 0.500 inches 1st end Straight St end Guine layer molded rubber, synthetic and 1st layer braided textile yarn Maximum Operating Pressure: 200.0 pounds per square inch Thread Size: 0.500 inches 1st end Stat Angle: 45.0 degrees 1st end Inside Surface Condition: Smoth Measuring Method And Length: 75.500 inches
Thread Direction: Right-hand 1st end Inside Diameter: 0.500 inches Tempurature Rating: -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.750 inches Minimun Inside Bending Radius: 5.000 inches Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Burst Test Pressure: 500.0 pounds per square inch Layer Composition And Location: 0.000 pounds per square inch Straight 1st end Duter layer molded rubber, synthetic and 1st layer braided textile yam Maximum Operating Pressure: 200.0 pounds per square inch Straight 1st end Duter layer molded rubber, synthetic and 1st layer braided textile yam Maximum Operating Pressure: 200.0 pounds per square inch Straight 1st end Heise Surface Condition: Stot inches 1st end Heise Surface Condition: Stot inches 1st end Heise Surface Condition:
Right-hand 1st end Inside Diameter: 0.500 inches Tempurature Rating: -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.750 inches Minimun Inside Bending Radius: 5.000 inches Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Donnection Type: Threaded external pipe 1st end Burst Test Pressure: 500.0 pounds per square inch Hayer Composition And Location: Outer layer molded rubber, synthetic and 1st layer braided textile yam Maximum Operating Pressure: 90.0 pounds per square inch External Steind Inside Surface Condition: 9.500 inches 1st end Stat Angle: 45.0 degrees 1st end Hiside Surface Condition: Smooth Measuring Method And Length: 75.500 inches
Inside Diameter: 0.500 inches Tempurature Rating: -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.750 inches Minimun Inside Bending Radius: 5.000 inches Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Portection Type: Threaded external pipe 1st end Burst Test Pressure: So0.0 pounds per square inch Haximun Operating Pressure: 200.0 pounds per square inch Straight 1st end Duter layer molded rubber, synthetic and 1st layer braided textile yam Maximun Operating Pressure: 200.0 pounds per square inch Extrema Size: 0.500 inches 1st end Sto degrees 1st end Heide Surface Condition: Smoth Measuring Method And Length: 75.500 inches
0.500 inches Fampurature Rating: -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diamete: 0.750 inches Minimun Inside Bending Radius: 5.000 inches Connection Style: Inverted flare 1st endEnd Connection Design:Straight 1st end Connection Type: Threaded external pipe 1st endBurst Test Pressure:200.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber, synthetic and 1st layer braided textile yarnMaximum Operating Pressure:20.0.0 pounds per square inch Straigen: 15.000 inches 1st end Burst Test Pressure: 20.0.1 pounds per square inch Chread Size: 20.0.1 pounds per square inch Straigen: 15.000 inches 1st end Burst Test Pressure: 20.0.1 pounds per square inch Bursting Method And Length: 75.00 inchesStraigen:15.000 inches 1st endStol degrees 1st end Straigen: Straigen:Stol inchesStol inches
Tempurature Rating: -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.750 inches Minimum Inside Bending Radius: 5.000 inches Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Burst Test Pressure: 500.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber, synthetic and 1st layer braided textile yam Maximum Operating Pressure: 20.00 pounds per square inch Statagh: 45.0 degrees 1st end Bist Exer 0.500 inches 1st end Statagh: 45.0 degrees 1st end Inside Surface Condition: Smoth Measuring Method And Length: 75.500 inches Special Features:
40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.750 inches Minimun Inside Bending Radius: 5.000 inches Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Burst Test Pressure: 500.0 pounds per square inch Layer Composition And Location: Outside Statend Straight 1st end Burst Test Pressure: 500.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber, synthetic and 1st layer braided textile yarn Maximum Operating Pressure: 200.0 pounds per square inch Stat Angle: 45.0 degrees 1st end Inside Surface Condition: Smoth Measuring Method And Length: 75.500 inches Special Features:
Outside Diameter: 0.750 inches Minimun Inside Bending Radius: 5.000 inches Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Burst Test Pressure: 500.0 pounds per square inch Layer Composition And Location: Outsel ayer molded rubber, synthetic and 1st layer braided textile yarn Maximum Operating Pressure: 200.0 pounds per square inch Extract Size: 0.500 inches 1st end Seat Angle: 45.0 degrees 1st end Inside Surface Condition: Smoth Measuring Method And Length: 75.500 inches Special Features:
0.750 inches Minimun Inside Bending Radius: 5.000 inches Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Burst Test Pressure: 500.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber, synthetic and 1st layer braided textile yam Maximum Operating Pressure: 200.0 pounds per square inch Thread Size: 0.500 inches 1st end Seat Angle: 45.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 75.500 inches
Minimum Inside Bending Radius: 5.000 inches Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Burst Test Pressure: 500.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber, synthetic and 1st layer braided textile yam Maximum Operating Pressure: 200.0 pounds per square inch Thread Size: 0.500 inches 1st end Seat Angle: 45.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 75.500 inches Special Features:
 5.000 inches Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Burst Test Pressure: 500.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber, synthetic and 1st layer braided textile yarn Maximum Operating Pressure: 200.0 pounds per square inch Thread Size: 0.500 inches 1st end Set Angle: 45.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 75.500 inches
Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Burst Test Pressure: 500.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber, synthetic and 1st layer braided textile yarn Maximum Operating Pressure: 200.0 pounds per square inch Thread Size: 0.500 inches 1st end Best Angle: 45.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 75.500 inches Special Features:
Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Burst Test Pressure: 500.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber, synthetic and 1st layer braided textile yarn Maxinum Operating Pressure: 200.0 pounds per square inch Thread Size: 0.500 inches 1st end Seat Angle: 45.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 75.500 inches
End Connection Design:Straight 1st endConnection Type:Threaded external pipe 1st endBurst Test Pressure:500.0 pounds per square inchLayer Composition And Location:Outer layer molded rubber, synthetic and 1st layer braided textile yarnMaximum Operating Pressure:200.0 pounds per square inchStried Size:0.500 inches 1st endSeat Angle:45.0 degrees 1st endSmoothMeasuring Method And Length:75.500 inchesSpecial Features:
Straight 1st endConnection Type:Threaded external pipe 1st endBurst Test Pressure:500.0 pounds per square inchLayer Composition And Location:Outer layer molded rubber, synthetic and 1st layer braided textile yarnMaximum Operating Pressure:200.0 pounds per square inchThread Size:0.500 inches 1st endSeat Angle:45.0 degrees 1st endInside Surface Condition:SmoothMeasuring Method And Length:75.500 inches
Connection Type:Threaded external pipe 1st endBurst Test Pressure:500.0 pounds per square inchLayer Composition And Location:Outer layer molded rubber, synthetic and 1st layer braided textile yarnMaximum Operating Pressure:200.0 pounds per square inchThread Size:0.500 inches 1st endSeat Angle:45.0 degrees 1st endInside Surface Condition:SmoothMeasuring Method And Length:75.500 inchesSpecial Features:
Threaded external pipe 1st end Burst Test Pressure: 500.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber, synthetic and 1st layer braided textile yarn Outer layer molded rubber, synthetic and 1st layer braided textile yarn Maximum Operating Pressure: 200.0 pounds per square inch Thread Size: 0.500 inches 1st end Seat Angle: 45.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 75.500 inches
Burst Test Pressure:500.0 pounds per square inchLayer Composition And Location:Outer layer molded rubber, synthetic and 1st layer braided textile yarnMaximum Operating Pressure:200.0 pounds per square inchThread Size:0.500 inches 1st endSeat Angle:45.0 degrees 1st endInside Surface Condition:SmoothMeasuring Method And Length:75.500 inchesSpecial Features:
 500.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber, synthetic and 1st layer braided textile yarn Maximum Operating Pressure: 200.0 pounds per square inch Thread Size: 0.500 inches 1st end Seat Angle: 45.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 75.500 inches Special Features:
Layer Composition And Location:Outer layer molded rubber, synthetic and 1st layer braided textile yarnMaximum Operating Pressure:200.0 pounds per square inchThread Size:0.500 inches 1st endSeat Angle:45.0 degrees 1st endInside Surface Condition:SmoothMeasuring Method And Length:75.500 inchesSpecial Features:
Outer layer molded rubber, synthetic and 1st layer braided textile yarnMaximum Operating Pressure:200.0 pounds per square inchThread Size:0.500 inches 1st endSeat Angle:45.0 degrees 1st endInside Surface Condition:SmoothMeasuring Method And Length:75.500 inchesSpecial Features:
Maximum Operating Pressure:200.0 pounds per square inchThread Size:0.500 inches 1st endSeat Angle:45.0 degrees 1st endInside Surface Condition:SmoothMeasuring Method And Length:75.500 inchesSpecial Features:
200.0 pounds per square inch Thread Size: 0.500 inches 1st end Seat Angle: 45.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 75.500 inches Special Features:
Thread Size: 0.500 inches 1st end Seat Angle: 45.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 75.500 inches Special Features:
0.500 inches 1st end Seat Angle: 45.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 75.500 inches Special Features:
Seat Angle:45.0 degrees 1st endInside Surface Condition:SmoothMeasuring Method And Length:75.500 inchesSpecial Features:
45.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 75.500 inches Special Features:
Inside Surface Condition: Smooth Measuring Method And Length: 75.500 inches Special Features:
Smooth Measuring Method And Length: 75.500 inches Special Features:
Measuring Method And Length: 75.500 inches Special Features:
75.500 inches Special Features:
Special Features:
Furnished w/brass fitting rdg e2 int thd 1/2-14 npt ext thd 1-1/16-f11-1/2 npsh
Media For Which Designed:
Fuel/oil, hydrocarbon and oil, lubricating, diester base and water single response
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:

NSN 4720-00-162-8314

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

