## NSN 4720-00-163-0283

Unef 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-163-0283

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.750 inches
Minimum Inside Bending Radius:
1.750 inches
Connection Style:
Swivel nut, compression 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
900.0 pounds per square inch
Layer Composition And Location:
2nd layer braided textile yarn and 3rd layer molded rubber, synthetic and 1st layer molded rubber, synthetic
Maximum Operating Pressure:
225.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
24.500 inches
Seat Radius:
0.062 inches 1st end
Special Features:
W/steel, externally thd adapter, 0.750-20 unef thd to 0.250-18 npt thd
Media For Which Designed:
Air single response
Thread Series Designator:

## NSN 4720-00-163-0283

Nonmetallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0