NSN 4720-00-163-3082

Outer layer braided corrosion resistant steel wire

Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-163-3082

Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.895 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Flange Thickness:
0.312 inches 2nd end
Outside Diameter:
1.156 inches
Minimum Inside Bending Radius:
7.380 inches
Center To Center Distance Between Bolt Holes Along Width:
1.313 inches 2nd end
Center To Center Distance Between Bolt Holes Along Length:
1.313 inches 2nd end
Bolt Hole Quantity:
4 2nd end
Flange Length:
1.750 inches 2nd end
Flange Width:
1.750 inches 2nd end
Connection Style:
Swivel nut flare 1st end
Bolt Hole Diameter:
0.188 inches 2nd end
End Flange Construction:
Solid 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Thready Qty Per Inch (tpi):
12 1st end
Laver Composition And Location:

NSN 4720-00-163-3082

Nonmetallic Hose Assembly - Page 2 of 2



Maximum Operating Pressure:
150.0 pounds per square inch
Thread Size:
1.313 inches 1st end
Seat Angle:
37.0 degrees 1st end
Flow Angle:
45.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
11.500 inches working
Flange Style:
Rectangular (includes square) 2nd end
Thread Series Designator:
Un 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0