NSN 4720-00-163-5838

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-163-5838 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.375 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** 0.625 inches **Minimum Inside Bending Radius:** 3.000 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Electrostatic discharge capability **Burst Test Pressure:** 1600.0 pounds per square inch **Layer Composition And Location:** Outer layer molded rubber, synthetic and 1st layer braided fiber **Maximum Operating Pressure:** 400.0 pounds per square inch **Thread Size:** 0.625 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 800.0 pounds per square inch **Outer Covering Environmental Protection:** Fuel resistant and oil resistant

Inside Surface Condition: Smooth Measuring Method And Length: 18.000 inches Thread Series Designator:

Unf 1st end

NSN 4720-00-163-5838

Nonmetallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0