NSN 4720-00-164-2882



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-164-2882 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response **Outside Diameter:** 0.781 inches **Minimum Inside Bending Radius:** 4.000 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 1600.0 pounds per square inch **Layer Composition And Location:** Outer layer molded rubber, synthetic and 1st layer braided rayon cord **Maximum Operating Pressure:** 400.0 pounds per square inch **Thread Size:** 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:**

800.0 pounds per square inch **Outer Covering Environmental Protection:** Oil resistant and ozone resistant and weatherproof **Inside Surface Condition:** Smooth **Measuring Method And Length:** 39.000 inches

Special Features:

Unf 1st end

Permanently attached fittings **Thread Series Designator:**

NSN 4720-00-164-2882

Nonmetallic Hose Assembly - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0