NSN 4720-00-164-3789



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-164-3789 **Cross Sectional Shape:** Round **Thread Class:** 2a 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.125 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.370 inches **Minimum Inside Bending Radius:** 1.500 inches **Exterior Color:** Black **Connection Style:** Swivel nut, inverted flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded external tube 1st end Thready Qty Per Inch (tpi): 24 1st end **Burst Test Pressure:** 4000.0 pounds per square inch **Layer Composition And Location:** Outer layer molded rubber, synthetic and 1st layer braided fabric **Maximum Operating Pressure:** 1000.0 pounds per square inch **Thread Size:** 0.437 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 2000.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:**

13.000 inches

Special Features:

Not for use w/unleaded or gasohol fuels

NSN 4720-00-164-3789

Nonmetallic Hose Assembly - Page 2 of 2



N	Λ	edia	For	Which	Design	ed

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Uns 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0