## NSN 4720-00-165-0950

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-165-0950 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.219 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response **Outside Diameter:** 0.438 inches **Minimum Inside Bending Radius:** 2.000 inches **Exterior Color:** Natural **Connection Style:** Swivel nut flare 2nd end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 6000.0 pounds per square inch **Layer Composition And Location:** Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire, partial coverage **Maximum Operating Pressure:** 1000.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 37.0 degrees 2nd end **Hydrostatic Test Pressure:** 3000.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end **Outer Covering Environmental Protection:** Corrosion resistant and fire resistant **Vacuum In Torr:** 

76.2

**Inside Surface Condition:** 

Smooth

## NSN 4720-00-165-0950

Nonmetallic Hose Assembly - Page 2 of 2



## Measuring Method And Length: 12.125 inches working Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unjf 1st end Specification Data: 81349-mil-h-83796/1 government specification Shelf Life: N/a Unit Of Measure: - Demilitarization:

No Fiig: A542a0