## NSN 4720-00-166-5888

Nonmetallic Hose - Page 1 of 2

**Cross Sectional Shape:** 



View Online at https://aerobasegroup.com/nsn/4720-00-166-5888

| Round   |
|---|
| Inside Diameter:  |
| 8.000 inches  |
| Tempurature Rating:   |
| -40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response |
| Outside Diameter:   |
| 8.940 inches  |
| Minimum Inside Bending Radius:  |
| 54.000 inches   |
| Exterior Color:   |
| Black   |
| Burst Test Pressure:  |
| 1200.0 pounds per square inch single response   |
| Layer Composition And Location:   |
| 1st layer braided textile yarn err-100  |
| Maximum Operating Pressure:   |
| 300.0 pounds per square inch single response  |
| Hydrostatic Test Pressure:  |
| 600.0 pounds per square inch single response  |
| Outer Covering Environmental Protection:  |
| Abrasion resistant and oxidation resistant and weatherproof                           |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 144.000 inches excluding end fittings   |
| Material:   |
| Rubber synthetic tube   |
| Media For Which Designed:   |
| Fuel/oil, hydrocarbon single response   |
| Specification Data:   |
| 81349-mil-h-24136 government specification  |
| Specification Or Standard:  |
| 128 size  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A541z0  |

## NSN 4720-00-166-5888

Nonmetallic Hose - Page 2 of 2



Mil-std (military Standard):

Mil-h-24136 spec.