NSN 4720-00-169-7435

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-169-7435

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.395 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response
Outside Diameter:
0.765 inches
Minimum Inside Bending Radius:
5.750 inches
Hose Or Tubing Specification/std Data:
Mil-h-38360, size 8 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting stainless steel all ends
Fitting Component And Surface Treatment:
Complete fitting passivate 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
20 2nd end
Second End Relationship With First End:
Not identical
Burst Test Pressure:
14000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire

0.750 inches 2nd end

Thread Size:

Maximum Operating Pressure: 3000.0 pounds per square inch

NSN 4720-00-169-7435

Nonmetallic Hose Assembly - Page 2 of 2



External Protection Type And Location (non-core):
chafe guard, polytetrafluoroethylene tubing
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Flow Angle:
45.0 degrees 2nd end
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
30.750 inches working
Second End Swivel Action Capability:
Not included
Special Features:
External protection type and location- chafe guard, polytetrafluoroethylene tubing, inner conveying tube material-plastic,
polytetrafluoroethylene
Thread Series Designator:
Un 2nd end
Specification Data:
Mil-h-38360, size 8 professional/industrial association specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0
Mil-std (military Standard):
Mil-h-38360 spec.