## NSN 4720-00-172-5605

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-172-5605

Cross Sectional Shape: Round Thread Direction: Right-hand 1st end Inside Diameter: 0.375 inches Tempurature Rating: -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response Outside Diameter: 0.656 inches Minimum Inside Bending Radius: 5.000 inches Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 2nd layer braided steel wire and outer layer molded rubber, chloroprene and 1st layer braided steel wire Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 0.375 inches 1st end Evert Test Pressure: 30.0 degrees 1st end Hydrostatic Test Pressure:						
Thread Direction: Right-hand 1st end Inside Diameter: 0.375 inches Tempurature Rating: -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response Outside Diameter: 0.656 inches Minimum Inside Bending Radius: 5.000 inches Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 2nd layer braided steel wire and outer layer molded rubber, chloroprene and 1st layer braided steel wire Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 0.375 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure:						
Right-hand 1st end Inside Diameter:  0.375 inches  Tempurature Rating: -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response  Outside Diameter:  0.656 inches  Minimum Inside Bending Radius:  5.000 inches  Connection Style: Inverted flare 1st end End Connection Design:  Straight 1st end  Connection Type: Threaded external pipe 1st end  Burst Test Pressure:  16000.0 pounds per square inch  Layer Composition And Location:  2nd layer braided steel wire and outer layer molded rubber, chloroprene and 1st layer braided steel wire  Maximum Operating Pressure:  4000.0 pounds per square inch  Thread Size:  0.375 inches 1st end  Seat Angle:  30.0 degrees 1st end  Hydrostatic Test Pressure:						
Inside Diameter:  0.375 inches  Tempurature Rating: -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response  Outside Diameter:  0.656 inches  Minimum Inside Bending Radius: 5.000 inches  Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end  Connection Type: Threaded external pipe 1st end  Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 2nd layer braided steel wire and outer layer molded rubber, chloroprene and 1st layer braided steel wire  Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 0.375 inches 1st end  Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure:						
Tempurature Rating: -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response  Outside Diameter: 0.656 inches  Minimum Inside Bending Radius: 5.000 inches  Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end  Connection Type: Threaded external pipe 1st end  Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 2nd layer braided steel wire and outer layer molded rubber, chloroprene and 1st layer braided steel wire  Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 0.375 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure:						
Tempurature Rating: -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response  Outside Diameter: 0.656 inches  Minimum Inside Bending Radius: 5.000 inches  Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end  Connection Type: Threaded external pipe 1st end  Burst Test Pressure: 16000.0 pounds per square inch  Layer Composition And Location: 2nd layer braided steel wire and outer layer molded rubber, chloroprene and 1st layer braided steel wire  Maximum Operating Pressure: 4000.0 pounds per square inch  Thread Size: 0.375 inches 1st end  Seat Angle: 30.0 degrees 1st end  Hydrostatic Test Pressure:						
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response  Outside Diameter:  0.656 inches  Minimum Inside Bending Radius: 5.000 inches  Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end  Connection Type: Threaded external pipe 1st end  Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 2nd layer braided steel wire and outer layer molded rubber, chloroprene and 1st layer braided steel wire  Maximum Operating Pressure: 4000.0 pounds per square inch  Thread Size: 0.375 inches 1st end  Seat Angle: 30.0 degrees 1st end  Hydrostatic Test Pressure:						
Outside Diameter:  0.656 inches  Minimum Inside Bending Radius:  5.000 inches  Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 2nd layer braided steel wire and outer layer molded rubber, chloroprene and 1st layer braided steel wire Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 0.375 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure:						
Minimum Inside Bending Radius: 5.000 inches Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 2nd layer braided steel wire and outer layer molded rubber, chloroprene and 1st layer braided steel wire Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 0.375 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure:						
Minimum Inside Bending Radius: 5.000 inches  Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 2nd layer braided steel wire and outer layer molded rubber, chloroprene and 1st layer braided steel wire Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 0.375 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure:						
5.000 inches  Connection Style: Inverted flare 1st end  End Connection Design: Straight 1st end  Connection Type: Threaded external pipe 1st end  Burst Test Pressure: 16000.0 pounds per square inch  Layer Composition And Location: 2nd layer braided steel wire and outer layer molded rubber, chloroprene and 1st layer braided steel wire  Maximum Operating Pressure: 4000.0 pounds per square inch  Thread Size: 0.375 inches 1st end  Seat Angle: 30.0 degrees 1st end  Hydrostatic Test Pressure:						
Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 2nd layer braided steel wire and outer layer molded rubber, chloroprene and 1st layer braided steel wire Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 0.375 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure:						
Inverted flare 1st end  End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 2nd layer braided steel wire and outer layer molded rubber, chloroprene and 1st layer braided steel wire Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 0.375 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure:						
End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 2nd layer braided steel wire and outer layer molded rubber, chloroprene and 1st layer braided steel wire Maximum Operating Pressure: 4000.0 pounds per square inch Thread Size: 0.375 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure:						
Straight 1st end  Connection Type: Threaded external pipe 1st end  Burst Test Pressure: 16000.0 pounds per square inch  Layer Composition And Location: 2nd layer braided steel wire and outer layer molded rubber, chloroprene and 1st layer braided steel wire  Maximum Operating Pressure: 4000.0 pounds per square inch  Thread Size: 0.375 inches 1st end  Seat Angle: 30.0 degrees 1st end  Hydrostatic Test Pressure:						
Connection Type: Threaded external pipe 1st end  Burst Test Pressure: 16000.0 pounds per square inch  Layer Composition And Location: 2nd layer braided steel wire and outer layer molded rubber, chloroprene and 1st layer braided steel wire  Maximum Operating Pressure: 4000.0 pounds per square inch  Thread Size: 0.375 inches 1st end  Seat Angle: 30.0 degrees 1st end  Hydrostatic Test Pressure:						
Threaded external pipe 1st end  Burst Test Pressure:  16000.0 pounds per square inch  Layer Composition And Location:  2nd layer braided steel wire and outer layer molded rubber, chloroprene and 1st layer braided steel wire  Maximum Operating Pressure:  4000.0 pounds per square inch  Thread Size:  0.375 inches 1st end  Seat Angle:  30.0 degrees 1st end  Hydrostatic Test Pressure:						
Burst Test Pressure:  16000.0 pounds per square inch  Layer Composition And Location:  2nd layer braided steel wire and outer layer molded rubber, chloroprene and 1st layer braided steel wire  Maximum Operating Pressure:  4000.0 pounds per square inch  Thread Size:  0.375 inches 1st end  Seat Angle:  30.0 degrees 1st end  Hydrostatic Test Pressure:						
16000.0 pounds per square inch  Layer Composition And Location:  2nd layer braided steel wire and outer layer molded rubber, chloroprene and 1st layer braided steel wire  Maximum Operating Pressure:  4000.0 pounds per square inch  Thread Size:  0.375 inches 1st end  Seat Angle:  30.0 degrees 1st end  Hydrostatic Test Pressure:						
Layer Composition And Location:  2nd layer braided steel wire and outer layer molded rubber, chloroprene and 1st layer braided steel wire  Maximum Operating Pressure:  4000.0 pounds per square inch  Thread Size:  0.375 inches 1st end  Seat Angle:  30.0 degrees 1st end  Hydrostatic Test Pressure:						
2nd layer braided steel wire and outer layer molded rubber, chloroprene and 1st layer braided steel wire  Maximum Operating Pressure:  4000.0 pounds per square inch  Thread Size:  0.375 inches 1st end  Seat Angle:  30.0 degrees 1st end  Hydrostatic Test Pressure:						
Maximum Operating Pressure:  4000.0 pounds per square inch  Thread Size:  0.375 inches 1st end  Seat Angle:  30.0 degrees 1st end  Hydrostatic Test Pressure:						
4000.0 pounds per square inch  Thread Size: 0.375 inches 1st end  Seat Angle: 30.0 degrees 1st end  Hydrostatic Test Pressure:						
Thread Size:  0.375 inches 1st end  Seat Angle:  30.0 degrees 1st end  Hydrostatic Test Pressure:						
0.375 inches 1st end  Seat Angle: 30.0 degrees 1st end  Hydrostatic Test Pressure:						
Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure:						
30.0 degrees 1st end  Hydrostatic Test Pressure:						
Hydrostatic Test Pressure:						
Inside Surface Condition:						
Smooth						
Measuring Method And Length:						
180.000 inches						
Special Features:						
Both ends furnished with a steel spring, 1.125 in od, 0.100 in wire @dia, 18.000 in free lg, 12.000 in installed lg						
Media For Which Designed:						
Fuel/oil, hydrocarbon single response						
Thread Series Designator:						
Nptf 1st end						
Shelf Life:						
N/a						

## NSN 4720-00-172-5605

Nonmetallic Hose Assembly - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A542a0