Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-175-7702

Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
1.125 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit	and 275.0 degrees fahrenheit single response
Outside Diameter:	
1.500 inches	
Minimum Inside Bending	g Radius:
9.000 inches	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design	
Straight 1st end	
Connection Type:	
Threaded internal tube 1s	t end
Thready Qty Per Inch (tp	vi):
12 1st end	
Burst Test Pressure:	
2500.0 pounds per square	e inch
Layer Composition And	Location:
2nd layer braided steel wi	re and outer layer rubber impregnated braided cotton cord and 1st layer braided cotton cord
Maximum Operating Pre	ssure:
625.0 pounds per square	inch
Thread Size:	
1.625 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Outer Covering Environ	mental Protection:
Fuel resistant and hydrau	lic solution resistant and oil resistant
Vacuum In Torr:	
254.0	
Inside Surface Condition	1:
Smooth	
Measuring Method And	Length:
127.000 inches working	
Media For Which Design	led:
Air and fuel/oil, hydrocar	bon single response

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

**Thread Series Designator:** 

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0