NSN 4720-00-175-7720

Convoluted

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-175-7720

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 275.0 degrees fahrenheit single response
Outside Diameter:
0.750 inches
Minimum Inside Bending Radius:
1.000 inches
Exterior Color:
Green
End Application:
An/alq-119
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
16 1st end
Burst Test Pressure:
750.0 pounds per square inch
Layer Composition And Location:
Outer layer spirally wrapped polyamide fabric and 1st layer spirally wrapped polytetrafluoroethylene impregnated glass fiber
Maximum Operating Pressure:
200.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
400.0 pounds per square inch
Inside Surface Condition:

NSN 4720-00-175-7720

Nonmetallic Hose Assembly - Page 2 of 2



modeaning modera / and zongan	Measuring	Method	And	Length:
-------------------------------	-----------	--------	-----	---------

9.000 inches working

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0