Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-176-4451

Cross Sectional Shape: Round Round Thread Class: 3b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.219 Inches Tempurature Rating: -8.0 degrees fahrenheit and 250.0 degrees fahrenheit single response Outside Diameter: 0.438 Inches Naminum Inside Bending Radius: 2.000 inches Connection Design: Swivel nut flare 1st end Burst Test Pressure: 8000.0 pounds per square inch Burst Test Pressure: 1000.0 pounds per square inch Maximum Operating Pressure: 1000.0 pounds per square inch Rust Test Pressure: 1000.0 pounds per square inch Correctin Environmental Protec	
Thread Class: 3b Ist end Thread Direction: Right-hand Ist end Bidd Diameter: 0.219 Inches 0.219 Inches 0.438 Inches 0.438 Inches 0.438 Inches 0.438 Inches 0.438 Inches 0.430 Inches Ist and 0.430 Inches Ist and<	
Sl st and Insection: Righ-hand sta end Insich Dameter: 0.219 inches Computer Rating: 0.50 degrees fahrenheit and 250.0 degrees fahrenheit single response Outsie Diameter: 0.438 inches Minimun Inside Bending Radius: 2.000 inches Conection Style: Solviel nut flare 1st end Endoametic:Conoction Dosign: Threaded internal tube 1st end Bourston Style: None on tube 1st end Bourston Style: Conoction Type:Threaded internal tube 1st end Bourston Style: Outo pounds per square inch Layer Composition And Location: Outo apper square inch Staff Inder Stressure: 100.0 pounds per square inch Charder Stressure: 100.0 pounds per square inch Staff Inder Stressure: 100.0 pounds per square inch Charder Stressure: 100.0 pounds per square inch Charder Stressure: 100.0 pounds per square inch Staff Inder Stressure: 100.0 pounds per square inch Charder Stressure: 100.0 pounds per square inch Staff Inder Stressure: 101.0 pounds per square inch Staff Ind	
Tread Direction: Right-hand 1st end Right-hand 1st end Inside Diameter: 0.219 inches Tempurature Rating: -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response Outside Diameter: 0.438 inches Minimum Inside Bending Radius: 2.000 inches Connection Style: Statight 1st end End Connection Design: Straight 1st end Connection Design: Straight 1st end Boon pounds per square inch Ausr Test Pressure: 6000.0 pounds per square inch Layer Composition And Location: 0uter layer breaded corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire, partial coverage 000.0 pounds per square inch Layer Composition And Location: 0uter layer breaded corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire, partial coverage 100.0 pounds per square inch Harrend Size: 10.438 inches 1st end Hydrostatic Test Pressure: 10.00.0 pounds per square inch Hydrostatic Test Pressure: 10.00.0 pounds per square inch	Thread Class:
Right-hand 1st end Right-hand 1st end Right-hand 1st end 2.19 Inches 2.50 degrees fahrenheit and 250.0 degrees fahrenheit single response Outside Diamete: 0.438 Inches 8.10 degrees fahrenheit and 250.0 degrees fahrenheit single response Outside Diamete: 0.438 Inches 8.10 diamete: 2.001 inches Connection Style: Strick Int fare 1st end Bornection Design: Straight 1st end Connection Design: Straight 1st end Bust Test Pressure: 600.0 pounds per square inch Layer Composition And Location: 000.0 pounds per square inch Straight 1st end Straight 1st end 1000 pounds per square inch Check Instell 1000 pounds per square inch Straight 1st end Straight 1st end Straight 1st end 1000 pounds per square inch Check Instell 1000 pounds per square inch Straight 1st end Straight 1st end Strangle: 1000	
Jaide Diameter: 0.219 inches Deprature Rating: -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response Outside Diameter: 0.438 inches Minimum Inside Bending Radius: 2.000 inches Connection Style: Sivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire an	Thread Direction:
2.19 indes2.19 indes2.19 indes2.10 indes2.03 indes2.00 indes2.00 indes2.01 indes2.02 indes2.02 indes2.03 indes2.04 indes 2.04 inder 3.04 i	Right-hand 1st end
Fenpurature Rating: 65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response Outside Diameter: 0.438 inches Minum Inside Bending Radius: 2.000 inches Connection Style: Swirel nut flare fst end End Connection Design: Straight 1st end Pornection Type: Threaded internal tube 1st end Bouto pounds per square inch Bouto pounds per square inch Bouto pounds per square inch Outor apper braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire, partial coverage Maximum Operating Pressure: 1000.0 pounds per square inch Maximum Operating Pressure: 100.0 pounds per square inch Pure State: 100.0 pounds per square inch Pure State: 100.0 pounds per square inch Stat Angle: 10.1 Operating Pressure: 10.2 Operating Test Pressure: 10.3 Operating Pressure: 10.4 Degrees steed 10.5 Degrees steed Bioter Steed 10.6 Degrees tead 10.6 Degrees tead 10.6 Degrees te	Inside Diameter:
-bs.0 degrees fahrenheit and 250.0 degrees fahrenheit single response Outside Diameter: 0.438 inches Minimum Inside Bending Radius: 2.000 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 6000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire, partial coverage Maximum Operating Pressure: 1000.0 pounds per square inch Maximum Operating Pressure: 1003.0 pounds per square inch Pure State: 1004.0 pounds per square inch Pure State: 1030.0 pounds per square inch State: 1040.0 gounds per square inch Pure State: 1050.0 pounds per square inch Pure State: 1040.0 gounds per square inch Pure State: 1050.0 pounds per square inch Pure State: 1050.0 pounds per square inch Pure St	0.219 inches
Outside Diameter: 0.438 inches Minimum Inside Bending Radius: 2.000 inches Connection Style: Switel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 6000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel vire, partial coverage Maximum Operating Pressure: 1000.0 pounds per square inch Arreaded inches 1st end Straight 1st end Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel vire, partial coverage Maximum Operating Pressure: 1000.0 pounds per square inch Hydrostatic Test Pressure: 300.0 pounds per square inch Hydrostatic Test Pressure: 3000.0 pounds per square inch Duter Covering Environmental Protection: Corosion resistant Vacuum In Torr: 7a.2 Inside Surface Condition: Smoch Maxeuring Method And Length:	Tempurature Rating:
0438 incles Minimun Inside Bending Radius: 2000 incles Connection Style: Swivel nut flare 1st end Enconnection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 6000.0 pounds per square inch Layer Composition And Location: Nuter layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire, partial coverage Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 10.438 inches 1st end Pareade Size 20.438 inches 1st end 10.438 inches 1st end 10.438 inches 1st end 20.0 pounds per square inch 10.438 inches 1st end 20.438 inches 1st end 10.409 pounds per square inch 10.438 inches 1st end 20.0 pounds per square inch 10.100 pounds per square inch	-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Minimu Inside Bending Radius:2.000 inchesConnection Style:Stwiel nut flare 1st endEnconnection Design:Straight 1st endConnection Type:Threaded internal tube 1st endBurster Stressure:6000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire, partial coverage1000.0 pounds per square inchStread Streed1000.0 pounds per square inchStreed Steel1000.0 pounds per square inch1011Streed Steel10211021102110211022103210331033104410451045105010501051105210521053105410541054105410541054 <t< td=""><td>Outside Diameter:</td></t<>	Outside Diameter:
2000 inches2000 inchesConnection Style:Stridel nut flare 1st endEnconnection Design:2010 inches2010 inches	0.438 inches
Connection Skyle:Swivel nut flare 1st endEnd Connection Design:Straight 1st endConnection Type:Threaded internal tube 1st endBurst Test Pressure:6000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion and tot provided to	Minimum Inside Bending Radius:
Swivel nut fare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 6000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire, partial coverage Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 0000.0 pounds per square inch Corrosion resistant Vagrees 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 000.0 pounds per square inch Corrosion resistant Vacum In Tor: 76.2 Fision Factore Condition: Smoth Measuring Method And Length: 15.000 inches working Meine For Which Designed:	2.000 inches
Erd Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 6000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire, partial coverage Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Corrosion resistant Predective Evolution: 6.20 Bounds per square inch Thread Size: 1300.0 pounds per square inch Corrosion resistant Gours Covering Environmental Protection: Corrosion resistant Yacuum In Torr: 76.2 Inside Surface Condition: Smooth Measuring Method And Length: 15.000 inches working	Connection Style:
Straight 1st endConnection Type:Threaded internal tube 1st endBurst Test Pressure:6000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire, partial coverageMaximum Operating Pressure:1000.0 pounds per square inchThread Size:0.438 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:3000.0 pounds per square inchCuter Covering Environmental Protection:Corrosion resistantYacuum In Torr:76.2Fineide Surface Condition:SmoothMeasuring Method And Length:15.000 inches workingMedia For Which Designed:	Swivel nut flare 1st end
Connection Type:Threaded internal tube 1st endBurst Test Pressure:6000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire, partial coverageMaximum Operating Pressure:1000.0 pounds per square inchThread Size:0.438 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:300.0 pounds per square inchChere Covering Environmental Protection:Corrosion resistantPressure:76.2Fisde Surface Condition:SmothMeasuring Method And Length:15.000 inches workingMeasuring Method Step Signed:15.000 inches working	End Connection Design:
Threaded internal tube 1st end Burst Test Pressure: 6000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire, partial coverage Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Yacuum In Torr: 7.6.2 Binde Surface Condition: Smoth Masuring Method And Length: 15.000 inches working	Straight 1st end
Burst Test Pressure:6000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire, partial coverageMaximum Operating Pressure:1000.0 pounds per square inchThread Size:0.438 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:3000.0 pounds per square inchCuter Covering Environmental Protection:Corrosion resistantPresure:10.2Burst Covering Environmental Protection:76.2Inside Surface Condition:SonohMeasuring Method And Length:15.000 inches workingMethod Endersina15.000 inches working	Connection Type:
6000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire, partial coverageMaximum Operating Pressure:1000.0 pounds per square inchThread Size:0.438 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:3000.0 pounds per square inchCorrosion resistantHydrostatic Test Pressure:3000.0 pounds per square inchCorrosion resistantPacum In Torr:76.2Inside Surface Condition:SmothMeasuring Method And Length:15.000 inches workingMedia For Which Designed:	Threaded internal tube 1st end
Layer Composition And Location:Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire, partial coverageMaximum Operating Pressure:1000.0 pounds per square inchThread Size:0.438 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:0300.0 pounds per square inchOuter Covering Environmental Protection:Corrosion resistantYacuum In Torr:76.2Inside Surface Condition:SmoothMeasuring Method And Length:15.000 inches workingMedia For Which Designed:	Burst Test Pressure:
Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire, partial coverageMaximum Operating Pressure:1000.0 pounds per square inchThread Size:0.438 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:3000.0 pounds per square inchOuter Covering Environmental Protection:Corrosion resistantVacuum In Torr:76.2Inside Surface Condition:SmoothMeasuring Method And Length:15.000 inches workingMedia For Which Designed:	6000.0 pounds per square inch
Maximum Operating Pressure:1000.0 pounds per square inchThread Size:0.438 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:3000.0 pounds per square inchOuter Covering Environmental Protection:Corrosion resistantVacuum In Torr:76.2Inside Surface Condition:SmoothMeasuring Method And Length:15.000 inches workingMedia For Which Designed:	Layer Composition And Location:
1000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Corrosion resistant Vacuum In Torr: 76.2 Inside Surface Condition: Smooth Measuring Method And Length: 15.000 inches working Media For Which Designed:	Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire, partial coverage
Thread Size:0.438 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:3000.0 pounds per square inchOuter Covering Environmental Protection:Corrosion resistantVacuum In Torr:76.2Inside Surface Condition:SmoothMeasuring Method And Length:15.000 inches workingMedia For Which Designed:	Maximum Operating Pressure:
0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Corrosion resistant Yacuum In Torr: 76.2 Inside Surface Condition: Smooth Measuring Method And Length: 15.000 inches working Media For Which Designed:	1000.0 pounds per square inch
Seat Angle:37.0 degrees 1st endHydrostatic Test Pressure:3000.0 pounds per square inchOuter Covering Environmental Protection:Corrosion resistantVacuum In Torr:76.2Inside Surface Condition:SmoothMeasuring Method And Length:15.000 inches workingMedia For Which Designed:	Thread Size:
37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 76.2 Inside Surface Condition: Smooth Measuring Method And Length: 15.000 inches working Media For Which Designed:	0.438 inches 1st end
Hydrostatic Test Pressure:3000.0 pounds per square inchOuter Covering Environmental Protection:Corrosion resistantVacuum In Torr:76.2Inside Surface Condition:SmoothMeasuring Method And Length:15.000 inches workingMedia For Which Designed:	Seat Angle:
3000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 76.2 Inside Surface Condition: Smooth Measuring Method And Length: 15.000 inches working Media For Which Designed:	37.0 degrees 1st end
Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 76.2 Inside Surface Condition: Smooth Measuring Method And Length: 15.000 inches working Media For Which Designed:	Hydrostatic Test Pressure:
Corrosion resistant Vacuum In Torr: 76.2 Inside Surface Condition: Smooth Measuring Method And Length: 15.000 inches working Media For Which Designed:	3000.0 pounds per square inch
Vacuum In Torr: 76.2 Inside Surface Condition: Smooth Measuring Method And Length: 15.000 inches working Media For Which Designed:	Outer Covering Environmental Protection:
76.2 Inside Surface Condition: Smooth Measuring Method And Length: 15.000 inches working Media For Which Designed:	Corrosion resistant
Inside Surface Condition: Smooth Measuring Method And Length: 15.000 inches working Media For Which Designed:	Vacuum In Torr:
Smooth Measuring Method And Length: 15.000 inches working Media For Which Designed:	76.2
Measuring Method And Length: 15.000 inches working Media For Which Designed:	Inside Surface Condition:
15.000 inches working Media For Which Designed:	Smooth
15.000 inches working Media For Which Designed:	
Media For Which Designed:	
-	-
	Fuel/oil, hydrocarbon single response

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:

Unjf 1st end

Specification Data:

96906-ms87028 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0