Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-176-4549

Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.625 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response	
Outside Diameter:	
1.080 inches	
Minimum Inside Bending Radius:	
6.500 inches	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 2nd end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Reusable end fittings	
Thready Qty Per Inch (tpi):	
12 1st end	
Burst Test Pressure:	
6000.0 pounds per square inch	
Layer Composition And Location:	
Outer layer rubber impregnated fabric and 1st layer braided steel wire	
Maximum Operating Pressure:	
1500.0 pounds per square inch	
Thread Size:	
1.062 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressure:	
3000.0 pounds per square inch	
Flow Angle:	
90.0 degrees 1st end	
Vacuum In Torr:	
50.0	
Inside Surface Condition:	
Smooth	

Nonmetallic Hose Assembly - Page 2 of 2



## Measuring Method And Length:

15.000 inches working

## Thread Series Designator:

Unj 1st end

Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A542a0