

View Online at <https://aerobasegroup.com/nsn/4720-00-176-4554>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.880 inches

Temperature Rating:

-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

Outside Diameter:

1.230 inches

Minimum Inside Bending Radius:

7.380 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

3200.0 pounds per square inch

Layer Composition And Location:

2nd layer braided steel wire and outer layer braided cotton cord and 1st layer braided fabric

Maximum Operating Pressure:

800.0 pounds per square inch

Thread Size:

1.000 inches 2nd end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

1600.0 pounds per square inch

Vacuum In Torr:

254.0

Inside Surface Condition:

Smooth

Measuring Method And Length:

27.000 inches

Special Features:

With buty liner

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0