NSN 4720-00-176-4554



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-176-4554 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.880 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response **Outside Diameter:** 1.230 inches **Minimum Inside Bending Radius:** 7.380 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end **Burst Test Pressure:** 3200.0 pounds per square inch **Layer Composition And Location:** 2nd layer braided steel wire and outer layer braided cotton cord and 1st layer braided fabric **Maximum Operating Pressure:** 800.0 pounds per square inch **Thread Size:** 1.000 inches 2nd end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 1600.0 pounds per square inch **Vacuum In Torr:** 254.0 **Inside Surface Condition:** Smooth **Measuring Method And Length:**

27.000 inches

With buty liner

Special Features:

NSN 4720-00-176-4554

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Un 1st end
Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0