NSN 4720-00-177-0286

Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-177-0286 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.375 inches **Tempurature Rating:** -67.0 degrees fahrenheit and 158.0 degrees fahrenheit single response **Outside Diameter:** 0.578 inches **Minimum Inside Bending Radius:** 4.000 inches **Exterior Color:** Black **Connection Style:** Swivel nut with compression sleeve 2nd end **End Connection Design:** Straight 1st end **End Fitting Component And Material:** Complete fitting aluminum alloy all ends **Fitting Component And Surface Treatment:** Complete fitting anodize 1st end **Connection Type:** Threaded internal tube 1st end Second End Relationship With First End: Not identical **Burst Test Pressure:** 1000.0 pounds per square inch First End Swivel Action Capability: Not included **Layer Composition And Location:** Outer layer molded rubber, synthetic **Maximum Operating Pressure:** 150.0 pounds per square inch **Thread Size:**

0.562 inches 2nd end Seat Angle: 12.0 degrees 2nd end **Hydrostatic Test Pressure:** 300.0 pounds per square inch

NSN 4720-00-177-0286

Nonmetallic Hose Assembly - Page 2 of 2



Flow Angle:
45.0 degrees 2nd end
Outer Covering Environmental Protection:
Abrasion resistant and fuel resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
29.500 inches working
Second End Swivel Action Capability:
Not included
Special Features:
Inner conveying tube material-rubber, synthetic
Media For Which Designed:
Air and hydraulic fluid single response
Thread Series Designator:
Unf 2nd end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0