Page 1 of 2 atallic Hos Nor



Nonmetallic Hose Assembly - Page 1 of 2	Group
View Online at https://aerobasegroup.com/nsn/4720-00-179-6309	
Cross Sectional Shape:	
Round	
Thread Class:	
2b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.250 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response	
Outside Diameter:	
0.600 inches	
Minimum Inside Bending Radius:	
4.000 inches	
Exterior Color:	
Black	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Reusable end fittings	
Burst Test Pressure:	
20000.0 pounds per square inch	
Layer Composition And Location:	
2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic and 1st layer braided co	rrosion resistant steel wire
Maximum Operating Pressure:	
5000.0 pounds per square inch	
Thread Size:	
0.438 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressure:	
10000.0 pounds per square inch	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	

Measuring Method And Length:

153.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

**Thread Series Designator:** 

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0