Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-179-9763

Cross Sectiona	al Shape:
Round	
Thread Class:	
3b 1st end	
Thread Direction	on:
Right-hand 1st e	end
Inside Diamete	r:
0.188 inches	
Tempurature R	ating:
-40.0 degrees fa	ahrenheit and 275.0 degrees fahrenheit single response
Outside Diame	ter:
0.516 inches	
Minimum Insid	e Bending Radius:
3.000 inches	
Connection Sty	/le:
Swivel nut flare	1st end
End Connectio	n Design:
Straight 1st end	
Connection Ty	pe:
Threaded intern	al tube 1st end
Thready Qty Pe	er Inch (tpi):
20 1st end	
Burst Test Pres	ssure:
12000.0 pounds	per square inch
Layer Compos	ition And Location:
2nd layer braide	d steel wire and outer layer rubber impregnated braided cotton cord and 1st layer braided cotton cord
Maximum Oper	rating Pressure:
3000.0 pounds	per square inch
Thread Size:	
0.438 inches 1s	t end
Seat Angle:	
37.0 degrees 1s	at end
Outer Covering	g Environmental Protection:
Fuel resistant ar	nd hydraulic solution resistant and oil resistant
Vacuum In Tor	r:
50.8	
Inside Surface	Condition:
Smooth	
	hod And Length:
89.625 inches \	-
Media For Whie	-

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0