NSN 4720-00-179-9771

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-179-9771

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.406 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 275.0 degrees fahrenheit single response
Outside Diameter:
0.766 inches
Minimum Inside Bending Radius:
4.620 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
16 1st end
Burst Test Pressure:
8000.0 pounds per square inch
Layer Composition And Location:
2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord and 1st layer braided cotton cord
Maximum Operating Pressure:
2000.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
37.0 degrees 1st end
Outer Covering Environmental Protection:
Fuel resistant and hydraulic solution resistant and oil resistant
Vacuum In Torr:
50.8
Inside Surface Condition:
Smooth
Measuring Method And Length:
67.906 inches working
Media For Which Designed:

Air and fuel/oil, hydrocarbon single response

NSN 4720-00-179-9771

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Unjf 1st end
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0