Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-180-5676

Cross	s Sectional Shape:
Round	d
Threa	ad Direction:
Right-	-hand 1st end
Inside	e Diameter:
0.250	inches
Temp	purature Rating:
-65.0	degrees fahrenheit and 200.0 degrees fahrenheit single response
Outsi	ide Diameter:
0.688	inches
Minin	num Inside Bending Radius:
4.000	inches
Exter	ior Color:
Black	
Conn	ection Style:
Plain	2nd end
End C	Connection Design:
Straig	pht 1st end
Conn	ection Type:
Threa	aded external pipe 2nd end
Burst	t Test Pressure:
20000	0.0 pounds per square inch
Layer	r Composition And Location:
2nd la	ayer braided wire and outer layer molded rubber, synthetic and 1st layer braided wire
Maxir	mum Operating Pressure:
5000.	0 pounds per square inch
Threa	ad Size:
0.250	inches 1st end
Hydro	ostatic Test Pressure:
10000	0.0 pounds per square inch
Flow	Angle:
90.0 c	degrees 2nd end
Outer	r Covering Environmental Protection:
Weath	herproof
Inside	e Surface Condition:
Smoo	oth
Meas	uring Method And Length:
18.37	75 inches
Speci	ial Features:
Secor	nd end special type 90 degrees coupling
Media	a For Which Designed:
Hydra	aulic fluid single response

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

Thread Series Designator:

Npt 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0