Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-181-8881

Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
nside Diameter:	
0.313 inches	
Fempurature Rating:	
40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response	
Outside Diameter:	
0.672 inches	
Minimum Inside Bending Radius:	
4.000 inches	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Burst Test Pressure:	
0000.0 pounds per square inch	
_ayer Composition And Location:	
2nd layer braided corrosion resistant steel wire and outer layer rubber impregnated braided cotton cord and	1st layer braided cotton cord
Maximum Operating Pressure:	
2000.0 pounds per square inch	
Гhread Size:	
0.562 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressure:	
4500.0 pounds per square inch	
Duter Covering Environmental Protection:	
Mildew resistant and oil resistant	
/acuum In Torr:	
50.8	
nside Surface Condition:	
Smooth	
Measuring Method And Length:	
27.000 inches working	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	

Nonmetallic Hose Assembly - Page 2 of 2



**Thread Series Designator:** 

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0