NSN 4720-00-181-9335

Cross Sectional Shape:

Round

Thread Class: 2b 1st end

Thread Direction: Right-hand 1st end Inside Diameter: 0.173 inches

Tempurature Rating:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-181-9335

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.330 inches
Minimum Inside Bending Radius:
2.000 inches
Exterior Color:
Natural
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability and nuts drilled for lockwire
Burst Test Pressure:
2400.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
600.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
1200.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:
Smooth

NSN 4720-00-181-9335

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:
18.500 inches
Thread Series Designator:
Unf 2nd end
Shelf Life:

N/a **Unit Of Measure:**

Demilitarization:

No

Fiig:

A542a0