Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-182-8873

| <u> </u> | inco Socianal Shano. |
|----------|---|
| | ross Sectional Shape: |
| | bund |
| | nread Class: |
| | 1 St end |
| | nread Direction: |
| | ght-hand 1st end |
| | side Diameter: |
| | 665 inches |
| | empurature Rating: |
| | 5.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response |
| | utside Diameter: |
| | 140 inches |
| | inimum Inside Bending Radius: |
| | 750 inches |
| | onnection Style: |
| | vivel nut flare 2nd end |
| | nd Connection Design: |
| | raight 1st end |
| | onnection Type: |
| | areaded internal tube 1st end |
| | nready Qty Per Inch (tpi): |
| - | 5 1st end |
| | yer Composition And Location: |
| | uter layer braided corrosion resistant steel wire |
| Ma | aximum Operating Pressure: |
| 30 | 00.0 pounds per square inch |
| Tł | nread Size: |
| 1.(| 625 inches 1st end |
| Se | eat Angle: |
| 37 | 0.0 degrees 1st end |
| Hy | /drostatic Test Pressure: |
| 45 | 00.0 pounds per square inch |
| Fl | ow Angle: |
| 45 | 0.0 degrees 2nd end |
| M | easuring Method And Length: |
| 30 | 0.498 inches working |
| Tŀ | nread Series Designator: |
| Ur | n 2nd end |
| Sł | nelf Life: |
| N/ | a |
| Ur | nit Of Measure: |
| | |

NSN 4720-00-182-8873

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0