Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-182-8948

| Cross Sectional Shape:   |
|--|
| Round  |
| Thread Class:  |
| 3b 1st end   |
| Thread Direction:  |
| Right-hand 1st end   |
| Inside Diameter:   |
| 0.125 inches   |
| Tempurature Rating:  |
| -100.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response |
| Outside Diameter:  |
| 0.250 inches   |
| Minimum Inside Bending Radius:   |
| 2.000 inches   |
| Exterior Color:  |
| Natural  |
| Connection Style:  |
| Swivel nut flare 1st end   |
| End Connection Design:   |
| Straight 1st end   |
| Connection Type:   |
| Threaded internal tube 1st end   |
| Thready Qty Per Inch (tpi):  |
| 24 1st end   |
| Burst Test Pressure:   |
| 12000.0 pounds per square inch   |
| Layer Composition And Location:  |
| Outer layer braided corrosion resistant steel wire                                     |
| Maximum Operating Pressure:  |
| 1500.0 pounds per square inch  |
| Thread Size:   |
| 0.375 inches 1st end   |
| Seat Angle:  |
| 37.0 degrees 1st end   |
| Hydrostatic Test Pressure:   |
| 3000.0 pounds per square inch  |
| Outer Covering Environmental Protection:   |
| Corrosion resistant  |
| Inside Surface Condition:  |
| Smooth   |
| Measuring Method And Length:   |
| 11.000 inches working and 11.500 inches working  |
|  |

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

**Thread Series Designator:** 

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0