

View Online at <https://aerobasegroup.com/nsn/4720-00-182-9218>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.852 inches

Temperature Rating:

-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response

Outside Diameter:

1.390 inches

Minimum Inside Bending Radius:

9.625 inches

Exterior Color:

Natural

Angle Between Rigid Elbow Fittings In Deg:

327.0

Connection Style:

Swivel nut, flareless 1st end

End Connection Design:

Elbow 2nd end

End Fitting Component And Material:

Complete fitting stainless steel all ends

Fitting Component And Surface Treatment:

Complete fitting passivate 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Electrostatic discharge capability

Thready Qty Per Inch (tpi):

12 2nd end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

12000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

1.312 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Flow Angle:

45.0 degrees 2nd end

Outer Covering Environmental Protection:

Corrosion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

30.375 inches working

Second End Swivel Action Capability:

Not included

Special Features:

Inner conveying tube material-plastic, polytetrafluoroethylene

Supplementary Features:

This item has been reviewed for asbestos material; the current approved sources; 50599 and 78570 have indicated their part number contained asbestos prior to 1984; they continue to manufacture the same part number without asbestos after 1984

Thread Series Designator:

Unj 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0