

View Online at <https://aerobasegroup.com/nsn/4720-00-183-0864>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

Between 0.234 inches and 0.266 inches

**Temperature Rating:**

-67.0 degrees fahrenheit and 158.0 degrees fahrenheit single response

**Outside Diameter:**

Between 0.453 inches and 0.500 inches

**Minimum Inside Bending Radius:**

4.000 inches

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Burst Test Pressure:**

1250.0 pounds per square inch

**Layer Composition And Location:**

Outer layer molded rubber, synthetic and 1st layer braided cotton cord

**Maximum Operating Pressure:**

200.0 pounds per square inch

**Thread Size:**

0.438 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

400.0 pounds per square inch

**Outer Covering Environmental Protection:**

Abrasion resistant and weatherproof and oil resistant and water resistant

**Vacuum In Torr:**

254.0

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

6.000 inches working

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0