## NSN 4720-00-184-7569

**Cross Sectional Shape:** 

Round

Thread Class: 2a 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.510 inches

**Tempurature Rating:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-184-7569

-100.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.630 inches
Minimum Inside Bending Radius:
6.500 inches
Connection Style:
Swivel nut, inverted flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external tube 1st end
Features Provided:
Reusable end fittings
Thready Qty Per Inch (tpi):
18 1st end
Burst Test Pressure:
6000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.875 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Vacuum In Torr:
50.8
Inside Surface Condition:
Smooth
Measuring Method And Length:
46.000 inches

## NSN 4720-00-184-7569

Nonmetallic Hose Assembly - Page 2 of 2



Th.		Carias	Dania	
1111	reau	Series	Desig	mator.

Uns 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0