## NSN 4720-00-184-8264

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-184-8264

| Cross Sectional Shape:   |  |  |  |  |  |
|--|--|--|--|--|--|
| Round  |  |  |  |  |  |
| Thread Direction:  |  |  |  |  |  |
|  |  |  |  |  |  |
| Right-hand 1st end  Inside Diameter:   |  |  |  |  |  |
|  |  |  |  |  |  |
| 0.750 inches   |  |  |  |  |  |
| Tempurature Rating:  |  |  |  |  |  |
| -40.0 degrees celsius and 200.0 degrees celsius single response  |  |  |  |  |  |
| Outside Diameter:  |  |  |  |  |  |
| 1.250 inches   |  |  |  |  |  |
| Minimum Inside Bending Radius:   |  |  |  |  |  |
| 9.500 inches   |  |  |  |  |  |
| Exterior Color:  |  |  |  |  |  |
| Natural  |  |  |  |  |  |
| Connection Style:  |  |  |  |  |  |
| Plain 1st end  |  |  |  |  |  |
| End Connection Design:   |  |  |  |  |  |
| Straight 1st end   |  |  |  |  |  |
| Connection Type:   |  |  |  |  |  |
| Threaded external pipe 1st end   |  |  |  |  |  |
| Burst Test Pressure:   |  |  |  |  |  |
| 9000.0 pounds per square inch  |  |  |  |  |  |
| Layer Composition And Location:  |  |  |  |  |  |
| Outer layer braided steel wire and 1st layer braided steel wire  |  |  |  |  |  |
| Maximum Operating Pressure:  |  |  |  |  |  |
| 2250.0 pounds per square inch  |  |  |  |  |  |
| Thread Size:   |  |  |  |  |  |
| 0.750 inches 1st end   |  |  |  |  |  |
| Seat Angle:  |  |  |  |  |  |
| 30.0 degrees 1st end   |  |  |  |  |  |
| Hydrostatic Test Pressure:   |  |  |  |  |  |
| 4500.0 pounds per square inch  |  |  |  |  |  |
| Outer Covering Environmental Protection:   |  |  |  |  |  |
| Abrasion resistant and oil resistant and weatherproof  |  |  |  |  |  |
| Inside Surface Condition:  |  |  |  |  |  |
| Smooth   |  |  |  |  |  |
| Measuring Method And Length:   |  |  |  |  |  |
| 45.000 inches  |  |  |  |  |  |
| Media For Which Designed:  |  |  |  |  |  |
| Hydraulic fluid, phosphate-ester base and hydraulic fluid, silicate-ester base and fuel/oil, hydrocarbon single response |  |  |  |  |  |
| Thread Series Designator:  |  |  |  |  |  |
| Npt 1st end  |  |  |  |  |  |

## NSN 4720-00-184-8264

Nonmetallic Hose Assembly - Page 2 of 2



| _ |     |      |   |      |
|---|-----|------|---|------|
| c | hο  | JIF. |   | ife: |
| J | 116 |      | _ | HG.  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0