

View Online at <https://aerobasegroup.com/nsn/4720-00-185-2773>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.625 inches

**Temperature Rating:**

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

**Outside Diameter:**

0.781 inches

**Minimum Inside Bending Radius:**

6.500 inches

**Angle Between Rigid Elbow Fittings In Deg:**

95.0

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Elbow 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Electrostatic discharge capability

**Thready Qty Per Inch (tpi):**

12 1st end

**Burst Test Pressure:**

5000.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

1000.0 pounds per square inch

**Thread Size:**

1.062 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

2000.0 pounds per square inch

**Flow Angle:**

90.0 degrees 1st end

**Outer Covering Environmental Protection:**

Corrosion resistant

**Vacuum In Torr:**

50.8

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

51.500 inches working

**Thread Series Designator:**

Un 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0