

View Online at <https://aerobasegroup.com/nsn/4720-00-186-3926>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.219 inches

Temperature Rating:

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

0.440 inches

Minimum Inside Bending Radius:

2.000 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Reusable end fittings

Burst Test Pressure:

6000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire, partial coverage

Maximum Operating Pressure:

1000.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Outer Covering Environmental Protection:

Cold resistant and corrosion resistant and fuel resistant and oil resistant

Vacuum In Torr:

76.2

Inside Surface Condition:

Smooth

Measuring Method And Length:

20.875 inches working

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unjf 1st end

Specification Data:

81349-mil-h-83796 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0