Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-188-7754

Ŧ	mpuraturo Pating.		
	mpurature Rating:		
	ot rated		
-	utside Diameter:		
	ny acceptable		
	nimum Inside Bending Radius:		
	of rated		
	rst End Connection Type:		
	readed internal pipe		
F	rst End Thread Direction:		
R	ght-hand		
S	cond End Connection Type:		
Т	readed external pipe		
S	cond End Thread Direction:		
R	ght-hand		
F	rst End Connection Design:		
S	raight		
S	cond End Connection Design:		
S	raight		
S	cond End Relationship With First End:		
Ν	ot identical		
в	ırst Test Pressure:		
Ν	ot rated		
F	rst End Swivel Action Capability:		
	bt included		
М	aximum Operating Pressure:		
	bt rated		
F	rst End Thread Series Designator:		
N			
	rst End Thread Size:		
	250 inches		
	uter Covering Environmental Protection:		
	prasion resistant and oil resistant		
	cond End Thread Size:		
	250 inches		
-	cond End Thread Series Designator:		
N			
	side Surface Condition:		
	nooth		
	cond End Swivel Action Capability:		
	ot included		
	becial Features:		
F	tings attached w/clamps		



Media For Which Designed:

Fuel/oil, hydrocarbon

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0