NSN 4720-00-191-7067

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-191-7067 **Cross Sectional Shape:** Round **Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response **Outside Diameter:** 0.500 inches **Minimum Inside Bending Radius:** 3.375 inches **Connection Style:** Swivel nut, inverted flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded external tube 1st end **Burst Test Pressure:** 2000.0 pounds per square inch **Layer Composition And Location:** 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord and 1st layer braided textile yarn **Maximum Operating Pressure:** 500.0 pounds per square inch **Thread Size:** 0.500 inches 1st end Seat Angle: 45.0 degrees 1st end **Outer Covering Environmental Protection:** Oil resistant Vacuum In Torr: 50.8 **Inside Surface Condition:** Smooth **Measuring Method And Length:** 10.750 inches Media For Which Designed:

Unf 1st end

Fuel/oil, hydrocarbon single response

Thread Series Designator:

NSN 4720-00-191-7067

Nonmetallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0