## NSN 4720-00-191-7070

Air Duct Hose - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-191-7070

Round  Wall Thickness:  0.060 inches  Inside Diameter:  1.250 inches first end  Minimum Inside Bending Radius:  3.750 inches  Endlength:  1.500 inches both ends  Connection Style:  Round both ends  Connection Type:  Soft both ends
0.060 inches Inside Diameter: 1.250 inches first end Minimum Inside Bending Radius: 3.750 inches Endlength: 1.500 inches both ends Connection Style: Round both ends Connection Type:
Inside Diameter:  1.250 inches first end  Minimum Inside Bending Radius:  3.750 inches  Endlength:  1.500 inches both ends  Connection Style:  Round both ends  Connection Type:
1.250 inches first end  Minimum Inside Bending Radius: 3.750 inches  Endlength: 1.500 inches both ends  Connection Style: Round both ends  Connection Type:
Minimum Inside Bending Radius: 3.750 inches Endlength: 1.500 inches both ends Connection Style: Round both ends Connection Type:
3.750 inches  Endlength: 1.500 inches both ends  Connection Style: Round both ends  Connection Type:
Endlength:  1.500 inches both ends  Connection Style:  Round both ends  Connection Type:
1.500 inches both ends  Connection Style:  Round both ends  Connection Type:
Connection Style: Round both ends Connection Type:
Round both ends  Connection Type:
Connection Type:
Soft both ends
End Inside Diameter:
1.250 inches both ends
Maximum Operating Pressure:
50.0 pounds per square inch
Measuring Method And Length:
9.500 inches
Material:
Steel reinforcing wire and copper alloy reinforcing wire
Style Designator:
Helically wound continous wire supported
Specification Data:
80205-nas1370 through 1379 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A229a0