Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-192-7311

| Cross Sectional Shape:   |
|--|
| Round  |
| Thread Direction:  |
| Right-hand 1st end   |
| Inside Diameter:   |
| 0.250 inches   |
| Tempurature Rating:  |
| -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response                      |
| Outside Diameter:  |
| 0.688 inches   |
| Minimum Inside Bending Radius:   |
| 4.000 inches   |
| Exterior Color:  |
| Black  |
| Connection Style:  |
| Plain 1st end  |
| End Connection Design:   |
| Straight 1st end   |
| Connection Type:   |
| Threaded external pipe 1st end   |
| Burst Test Pressure:   |
| 20000.0 pounds per square inch   |
| Layer Composition And Location:  |
| 2nd layer braided wire and outer layer molded rubber, synthetic and 1st layer braided wire |
| Maximum Operating Pressure:  |
| 5000.0 pounds per square inch  |
| Thread Size:   |
| 0.250 inches 1st end   |
| Hydrostatic Test Pressure:   |
| 10000.0 pounds per square inch   |
| Outer Covering Environmental Protection:   |
| Weatherproof   |
| Inside Surface Condition:  |
| Smooth   |
| Measuring Method And Length:   |
| 40.500 inches  |
| Media For Which Designed:  |
| Hydraulic fluid single response  |
| Thread Series Designator:  |
| Anpt 1st end   |
| Shelf Life:  |
| N/a  |
|  |

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0