Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-192-9134

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 2b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.250 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.500 inches |
| Minimum Inside Bending Radius: |
| 3.000 inches |
| Exterior Color: |
| Black |
| Connection Style: |
| Swivel nut, inverted flare 2nd end |
| End Connection Design: |
| Straight 2nd end |
| Connection Type: |
| Threaded internal tube 1st end |
| Thready Qty Per Inch (tpi): |
| 24 2nd end |
| Burst Test Pressure: |
| 1000.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer molded rubber, synthetic and 1st layer braided rayon cord |
| Maximum Operating Pressure: |
| 250.0 pounds per square inch |
| Thread Size: |
| 0.437 inches 2nd end |
| Seat Angle: |
| 45.0 degrees 2nd end |
| Hydrostatic Test Pressure: |
| 500.0 pounds per square inch |
| Outer Covering Environmental Protection: |
| Abrasion resistant and mildew resistant and oil resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 20.500 inches |
| |

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:

Uns 2nd end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0