Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-193-3210

Cr	oss Sectional Shape:
Ro	bund
Th	read Class:
3b	1st end
Th	read Direction:
Riç	ght-hand 1st end
Ins	side Diameter:
0.2	212 inches
Те	mpurature Rating:
-65	5.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Ou	itside Diameter:
0.4	100 inches
Mi	nimum Inside Bending Radius:
1.5	500 inches
Co	onnection Style:
Sw	vivel nut flare 1st end
En	d Connection Design:
Str	raight 1st end
Co	onnection Type:
Th	readed internal tube 1st end
Fe	atures Provided:
Ele	ectrostatic discharge capability
Bu	irst Test Pressure:
12	000.0 pounds per square inch
La	yer Composition And Location:
Ou	ter layer braided corrosion resistant steel wire
Ма	aximum Operating Pressure:
30	00.0 pounds per square inch
Th	read Size:
0.4	138 inches 1st end
Se	at Angle:
37.	.0 degrees 1st end
Hy	drostatic Test Pressure:
60	00.0 pounds per square inch
Ou	Iter Covering Environmental Protection:
Co	prrosion resistant
Ins	side Surface Condition:
Sm	nooth
Me	easuring Method And Length:
19	.000 inches
Th	read Series Designator:
Un	jf 1st end

Nonmetallic Hose Assembly - Page 2 of 2



Specification Data:

81349-mil-h-38360 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-38360 spec.