Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-195-0099

Cross Sectional Shape:	
Round	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.188 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit s	single response
Outside Diameter:	
0.516 inches	
Minimum Inside Bending Radius:	
4.000 inches	
Exterior Color:	
Black	
Quick Disconnect Size:	
0.250 inches 2nd end	
Connection Style:	
Push (external) 2nd end	
End Connection Design:	
Straight 2nd end	
Connection Type:	
Threaded external pipe 1st end	
Features Provided:	
Reusable end fittings	
Burst Test Pressure:	
20000.0 pounds per square inch	
Layer Composition And Location:	
2nd layer braided steel wire and outer layer molded rubb	per, synthetic and 1st layer braided steel wire
Maximum Operating Pressure:	
5000.0 pounds per square inch	
Thread Size:	
0.250 inches 1st end	
Hydrostatic Test Pressure:	
10000.0 pounds per square inch	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
73.750 inches	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	
Thread Series Designator:	

NSN 4720-00-195-0099

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

