## NSN 4720-00-195-1634

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-195-1634

Cross Sectional Shape:				
Round				
Thread Class:				
3b 1st end				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.375 inches				
Tempurature Rating:				
-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response				
Outside Diameter:				
Between 0.620 inches and 0.640 inches				
Minimum Inside Bending Radius:				
2.000 inches				
Exterior Color:				
Black				
Connection Style:				
Swivel nut flare 1st end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded internal tube 1st end				
Thready Qty Per Inch (tpi):				
18 1st end				
Burst Test Pressure:				
9000.0 pounds per square inch				
Layer Composition And Location:				
Outer layer molded polyurethane and 1st layer braided polyamide cord				
Maximum Operating Pressure:				
2250.0 pounds per square inch				
Thread Size:				
0.562 inches 1st end				
Seat Angle:				
37.0 degrees 1st end				
Hydrostatic Test Pressure:				
4500.0 pounds per square inch				
Outer Covering Environmental Protection:				
Abrasion resistant				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				

13.875 inches and 14.125 inches

## NSN 4720-00-195-1634

Nonmetallic Hose Assembly - Page 2 of 2



_	brood	Carias	Docionatori
ı	meau	oenes	Designator:

Unf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0