NSN 4720-00-195-5761

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-195-5761

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.688 inches
Minimum Inside Bending Radius:
5.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
9000.0 pounds per square inch
Layer Composition And Location:
Outer layer molded rubber, synthetic and 1st layer braided steel wire
Maximum Operating Pressure:
2250.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
4500.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and cold resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
31.000 inches
Media For Which Designed:
Hydraulic fluid single response
Tydradile had single response

NSN 4720-00-195-5761

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designat	or:
------------------------	-----

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0