## NSN 4720-00-195-5861

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-195-5861

| Cross Sectional Shape:  |  |
|---|--|
| Round   |  |
| Thread Class:   |  |
| 3b 1st end  |  |
| Thread Direction:   |  |
| Right-hand 1st end  |  |
| Inside Diameter:  |  |
| 0.093 inches  |  |
| Tempurature Rating:   |  |
| -40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response |  |
| Outside Diameter:   |  |
| 0.281 inches  |  |
| Minimum Inside Bending Radius:  |  |
| 1.500 inches  |  |
| Exterior Color:   |  |
| Natural   |  |
| Connection Style:   |  |
| Swivel nut flare 1st end  |  |
| End Connection Design:  |  |
| Straight 1st end  |  |
| Connection Type:  |  |
| Threaded internal tube 1st end  |  |
| Burst Test Pressure:  |  |
| 800.0 pounds per square inch  |  |
| Layer Composition And Location:   |  |
| Outer layer braided corrosion resistant steel wire                                    |  |
| Maximum Operating Pressure:   |  |
| 200.0 pounds per square inch  |  |
| Thread Size:  |  |
| 0.312 inches 1st end  |  |
| Seat Angle:   |  |
| 37.0 degrees 1st end  |  |
| Hydrostatic Test Pressure:  |  |
| 400.0 pounds per square inch  |  |
| Outer Covering Environmental Protection:  |  |
|   |  |

Corrosion resistant

Smooth

**Inside Surface Condition:** 

inside Surface Condit

**Measuring Method And Length:** 

7.312 inches excluding end fittings

Media For Which Designed:

Fuel/oil, hydrocarbon single response

## NSN 4720-00-195-5861

Nonmetallic Hose Assembly - Page 2 of 2



|   | ••  |    | •    | _      |      |        |
|---|-----|----|------|--------|------|--------|
| ı | hre | ลด | Seri | 26 I I | PSIU | nator: |
| • |     | uu | CCII |        | COIG | mator. |

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0