

View Online at <https://aerobasegroup.com/nsn/4720-00-195-6015>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.750 inches

Temperature Rating:

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

1.250 inches

Minimum Inside Bending Radius:

9.500 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

9000.0 pounds per square inch

Layer Composition And Location:

2nd layer braided steel wire and outer layer molded rubber, chloroprene and 1st layer braided steel wire

Maximum Operating Pressure:

2250.0 pounds per square inch

Thread Size:

1.062 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

4500.0 pounds per square inch

Outer Covering Environmental Protection:

Mildew resistant and oil resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

32.000 inches

Thread Series Designator:

Un 1st end

Specification Data:

81349-mil-h-13531 government specification

Specification Or Standard:

A class and 2 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-13531 spec.