

View Online at <https://aerobasegroup.com/nsn/4720-00-195-6015>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.750 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

**Outside Diameter:**

1.250 inches

**Minimum Inside Bending Radius:**

9.500 inches

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Thready Qty Per Inch (tpi):**

12 1st end

**Burst Test Pressure:**

9000.0 pounds per square inch

**Layer Composition And Location:**

2nd layer braided steel wire and outer layer molded rubber, chloroprene and 1st layer braided steel wire

**Maximum Operating Pressure:**

2250.0 pounds per square inch

**Thread Size:**

1.062 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

4500.0 pounds per square inch

**Outer Covering Environmental Protection:**

Mildew resistant and oil resistant and oil resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

32.000 inches

**Thread Series Designator:**

Un 1st end

**Specification Data:**

81349-mil-h-13531 government specification

**Specification Or Standard:**

A class and 2 type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0

**Mil-std (military Standard):**

Mil-h-13531 spec.