## NSN 4720-00-195-6586

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-195-6586
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.298 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
0.656 inches
Minimum Inside Bending Radius:
2.500 inches
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
14000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:

6000.0 pounds per square inch

**Outer Covering Environmental Protection:** 

Corrosion resistant

**Inside Surface Condition:** 

Smooth

**Measuring Method And Length:** 

23.750 inches working

**Thread Series Designator:** 

Unjf 1st end

## NSN 4720-00-195-6586

Nonmetallic Hose Assembly - Page 2 of 2



Spec	ifica	ation	Data:
------	-------	-------	-------

81343-as115 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0